

Verint S2101e-R-HD Decoder



Key Features:

- HDMI Output
- Displays up to 4 tiles at 1080p
- Enables organizations to realize the benefits of HD IP video
- Compatible with Verint EdgeVMS
- Compact, energy efficient, and environmentally friendly
- Web interface for easy implementation and configuration
- VESA mount and power supply included

Verint S2101e-R-HD Decoder

The Verint® S2101e-R-HD Decoder incorporates advanced H.264 decompression technology to deliver superior video quality for up to 4 HD (1080p) video tiles to an HDMI monitor making it useful in a variety of environments..

Designed to be able to display up to four HD (1080p) tiles on a high-definition HDMI LCD or plasma monitor. The S2101e-R-HD Decoder is a great choice for a remote monitor solution. It provides excellent video quality, high reliability and easy installation in a lightweight and compact design.

Advanced Video Technology with Lowest TCO

Verint is at the forefront of networked video technology, with over two decades of experience providing security intelligence solutions to government and industry worldwide. Using custom Dell hardware to power our software, the S2101e-R-HD Decoder is a versatile edge device built on the latest video technology, integrated with the industry's broadest video portfolio and built for easy installation and operation. Designed to enhance any video network, this decoder will help organizations realize the benefits of displaying HD IP video.

VERINT.

Verint S2101e-R-HD Decoder

VIDEO		ELECTRICAL	
Outputs/Connectors	HDMI out	Supply/Voltage	100-240v
Performance	4 x 1080p, 120FPS across the unit	Power Consumption	Max. 65W
Resolution	From CIF to 1080P (higher resolutions possible)	PHYSICAL	
Compression	H.264 (MPEG-4 Part 10/AVC) Main Profile	Dimensions	130 (W) x 107 (D) x 28 (H) mm
Tiles	Max of 4 tiles on 1 monitor • Display options of 1x1, 2x2	Weight	550g
NETWORK		Operating Temperature	5° to 35° C (41° to 95° F)
Interface	10/100/1000M Gigabit Ethernet	Humidity	95% (non-condensing)
Protocols	Transport: RTP/IP, UDP/IP, TCP/IP, RTSP, or multicast IP • Others: DNS, NTP, SNMP v1/v2c/v3 (MIB-II), HTTP, HTTPS, DHCP client, 802.1x	Firmware	Embedded Linux-based operating system
Security	SSL-based authentication, password protected, HTTPS	Accessories	Vesa Mount Included. Power supply included
SERIAL PORTS		Compliance	Certifications: CE, FCC, CB, LVD, UCKA Compliance: NDAA Compliant
Optional	USB to serial interface using the FTDI transceiver	* Features listed in this document are subject to change. Not all functionality is available in all configurations	
Operating Mode	Transparent serial port supporting any asynchronous serial protocol		
MANAGEMENT			
Configuration and Firmware Upgrade	Supported in Verint EdgeVMS, SConfigurator and Web browser interface (single device firmware upgrade)		



Learn more about Verint S2101e-R-HD Decoder at www.verint.com

The Customer Engagement Company™

Americas 9am – 5pm Local Time 1-888-585-7059 EdgeVMS.Support@verint.com	Europe, Middle East & Africa 8am – 6pm GMT +44 (0) 193 250 9000 EdgeVMS.GlobalSupport@verint.com	Asia Pacific 9am – 5pm SGT +44 (0) 193 250 9000 EdgeVMS.GlobalSupport@verint.com	 verint.com twitter.com/verint linkedin.com/company/verint verint.com/blog
---	--	--	--