

Verint V3422FDW



Key Features:

- 2MP(1920x1080)@30fps resolution
- Smart compression offering optimally useable bandwidth and storage
- H.265/H.264
- Built-in 2.8mm megapixel fixed lens
- Built-in IR illumination, effective up to 15 meters
- Ultra-discreet in style, very compact and flat for surface-mount installation
- True WDR 120dB for better visibility
- Micro SDHC/SDXC memory slot
- IP67/IK10
- PoE
- ONVIF Profile S

Verint V3422FDW

2MP • True WDR • AdaptiveStream • Small Form Factor

Verint® V3422FDW is a small, fixed dome HD network camera, offering superb image quality up to 2-megapixel resolution. Due to its discreet design the camera is able to blend into any indoor or outdoor surveillance space such as retail, banks, restaurants, offices and stand alone ATMs.


Featuring True WDR, the V3422FDW provides superior visibility in high-contrast lighting environments and high-quality full-color surveillance video even under low-light conditions. Armed with Verint's sophisticated AdaptiveStream technology, which allows the camera to optimize image quality for desired regions, reducing bandwidth while maintaining image quality and storage requirements.

Most importantly the V3422FDW is fully integrated into our Verint EdgeVR® platform making it easy to adjust and maintain over its life. The camera also features easy installation with Auto Camera Config, Remote Password and Firmware Update, HTTPS support for secure connections, integrated camera adjustment and more.

VERINT.®

V3422FDW Technical Specifications

CAMERA FEATURES		On Board Storage	
Image Sensor	1/2.8"	1 x micro SDHC/SDXC slot (card not included), Recording & Playback, SD card encryption Filesystem EXT4 support	
Lens Type	f2.8mm, F1.8, Fixed		
Field of View	109° (H), 59° (V)		
Minimum Illumination	Color: 0.00795 Lux F1.8, B/W: 0.00232 Lux IR		
Iris Mode	On, Off, Auto		
IR Distance	15m		
Smart IR	On, Off		
D/N Control	Mechanical D/N		
IMAGE		MECHANICAL	
Exposure Mode	Auto, Shutter-Priority, Manual, Flickerless, True WDR	Casing Material	
Shutter Speed	1/12 s~1/10000s	Metal Housing – Aluminum Alloy Dome Bubble – Polycarbonate	
WDR	True WDR, 120dB	Weathering Resistance	
Image Orientation	Off, Flip, Mirror, Both	IP67	
Privacy Zone	8 Zones	Vandal Resistance	
Image Setting	Gain Control, WB, BLC, HLC, Defog, EV, Gamma Correction, 3DNR, Sharpness, Brightness, Contrast, Hue, Saturation	IK10	
VIDEO		Dimension	
Video Compression	H.265/HEVC Main Profile H.264 Main/High/Baseline Profile	Ø110mmx57mm	
Maximum Frame Rate	3 simultaneous streams 1920x1080@30fps (H.264/H.265) Single: 2MP@30fps Dual: 2MP@30fps + 1280x720@15fps Triple: 2MP@30fps+ 1280x720@15fps+ 640x480@30fps	Weight (camera only)	
System Frequency	60Hz/50Hz	630g (Approx.)	
Enhanced Codec	Adaptivestream	ELECTRICAL	
Bitrate Control	CBR/CVBR (H.264: 64~20000bps, H.265 : 64~8000bps), VBR	Power Source	PoE
AUDIO		Power-over-Ethernet	IEEE 802.3af, Class 3
Compression Format	G.711 (a-law , u-law), Line in / out	Power Consumption	13.5W (Max)
NETWORK		ENVIRONMENTAL	
User Web Access	Up to 10 clients	Operating Temperature	-10°C ~ 55°C
Protocols	ARP, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4/6, LDAP, NTP, RTSP/RTCP/RTP, QoS, SMTP, SNMP v1/2c/3, TCP, TLS/TTLS, UDP, UPnP, 802.1X, Bonjour, SNMP v1/2c/3, DDNS, PPPoE	Cold Start Temperature	-20°C
Internet Security	IEEE 802.1X, HTTPS, Digest Authentication, IP Filtering, Advanced Security	Storage Temperature	-40°C ~ 60°C
GENERAL		Storage Humidity	90%, non-condensing



Learn more about Verint V3422FDW
at www.verint.com

The Customer Engagement Company™

Americas

info@verint.com

+1 770 754 1900

1-800-4VERINT

Europe, Middle East & Africa

info.emea@verint.com

+44(0) 1932 839500

Asia Pacific

info.apac@verint.com

+(852) 2797 5678



verint.com

twitter.com/verint

linkedin.com/company/verint

verint.com/blog