

# Verint V3920FDW



## Key Features:

- Max. 2MP(1920x1080)@30fps resolution
- H.264 compression reducing bandwidth and storage needs
- Built-in IR illumination, effective up to 30 meters
- Built-in megapixel motorized lens for remote zoom and focus
- Micro SDHC/SDXC memory slot
- True HDR for better visibility
- Smart Analytics featuring Intrusion detection, Loitering Detection, Line Crossing Detection, Unattended Object Detection, Missing Object Detection
- Powerful integration with our Verint EdgeVR recorders

## Verint V3920FDW

**2MP • POE • HDR • 30M IR • IP66 • IK10 • Remote Focus and Zoom • Built in Analytics**

The Verint® V3920FDW network dome camera can be used for indoor and outdoor installations. With a maximum resolution of 1920x1080 at 30 fps. The V3920FDW is a great camera with clear sharp images and features including High Dynamic Range (HDR), Remote Focus and Zoom and built-in smart analytics.

For protection against harsh outdoor environments, the camera is encased in a weather-proof IP66-rated housing, making it impervious to rain and dust. Also with its IK10 rating, the camera is vandal resistant and can withstand 20 Joules of impact.

Most importantly the V3920FDW is fully integrated into our Verint EdgeVR® platform making it easy to adjust and maintain over its life. The camera also features easy installation with Auto Camera Config, Remote Password and Firmware Update, HTTPS support for secure connections, integrated camera image adjustment and more.

**VERINT.®**

# V3920FDW Technical Specifications

OPTICAL		POWER	
Image Sensor	1/2.7" Progressive CMOS	Power Source	PoE 802.3af class 3, 12VDC
Effective Pixels	2Mp (1920H x 1080V)	Power Consumption	DV12V Max. 6.84W (IR on) PoE Max. 7.25W (IR on)
WDR Technology	HDR	INPUT/OUTPUT	
Focal Length	2.7~13.5mm	Connectivity	RJ-45, 10/100Mbps
Field of View	Diagonal 129 ~ 36° / Horizontal 106 ~ 31° / Vertical 55 ~ 17.5°	Connectors	Power = DC Jack, RJ-45 PoE Ethernet = RJ-45 Cable Alarm = DI x 1, DO x 1 Audio I/O = 3.5mm stereo audio jack x2
Ambient Light Sensor	Yes	On-Board Storage	MicroSD/SDHC/SDXC Card Slot
IR Cut Filter	Yes	INTELLIGENT SOLUTION	
IR LED		Event Application	Audio Detection, Camera Tampering Detection, Smart Motion Detection, Smart VCA
Type	Built-in IR Illuminators	Smart Motion Detection	Five-window Video Motion Detection, People Detection, Vehicle Detection
IR Distance	30M	Smart Analytics	Intrusion detection, Loitering Detection, Line Crossing Detection, Unattended Object Detection, Missing Object Detection
VIDEO		GENERAL	
Compression	H.264	Rotation	Pan = 353° Tilt = 75° Rotation = 350°
Enhanced Codec	Adaptivestream, Dynamic 3DNR	Operation Temperature	Start/Working = -30°C ~ 60°C
Bitrate Control	VBR, CBR	Condensation	90% R.H
Encode Performance	1080p@30fps + 1080p@30fps + 720p@30fps*	Vandal Resistance	IK10
IMAGE		Ingress Protection	IP66
Wide Dynamic Range	120dB	Dimensions	Ø 133.7 X 103.79mm
Image Orientation	Flip, Mirror, Both, Corridor	Weight	758g
Image Setting	White balance, Brightness, Contrast, Saturation, Sharpness, Gamma correction, defog	Package Contents	QIG, Installation Sticker, Screw Packs, Cable Gland, L-type Wrench, Plug
Privacy Masking	Yes	Compliance	Certifications: CE, FCC, UL, CB, UKCA, LVD, ICES Compliance: NDAA Compliant
Exposure Mode	Auto, Manual, HDR, BLC, HLC		
Shutter Speed	1/5 - 1/32000		
AUDIO			
Compression	G.711/G.726		
Microphone	Yes		
Audio Connections	Line In, Line Out		

\*Please contact sales representative for detail streaming combination performance.  
Product specification and availability are subject to change without notice.



Learn more about Verint V3920FDW  
at [www.verint.com](http://www.verint.com)

## The Customer Engagement Company™

Americas	Europe, Middle East & Africa	Asia Pacific	verint.com
9am – 5pm Local Time	8am – 6pm GMT	9am – 5pm SGT	<a href="http://twitter.com/verint">twitter.com/verint</a>
1-888-585-7059	+44 (0) 193 250 9000	+44 (0) 193 250 9000	<a href="http://linkedin.com/company/verint">linkedin.com/company/verint</a>
EdgeVMS.Support@verint.com	EdgeVMS.GlobalSupport@verint.com	EdgeVMS.GlobalSupport@verint.com	<a href="http://verint.com/blog">verint.com/blog</a>